

Produkte

Mainboard Serie

»960GM-GS3 FX

»Überblick

»Spezifikationen

»Download

»Handbuch

»FAQ

»CPU Support Liste

»Speicher Support Liste

»Beta-Zone

ASRock Channel on YouTube



facebook

Follow ASRock on facebook now!

ASRock Forum



960GM-GS3 FX

[Translate](#)

- Supports AM3+ Processor, 8-Core CPU
- Solid Capacitor for CPU Power
- Supports Dual Channel DDR3 1800(OC)
- 1 x PCI Express 2.0 x16 slot
- Integrated AMD Radeon 3000 graphics, DX10, PS 4.0
- Gigabit LAN 10/100/1000 Mb/s
- 5.1 CH HD Audio (Realtek ALC662 Audio Codec)
- Supports ASRock XFast RAM, XFast LAN, XFast USB Technologies
- Supports ASRock Instant Boot, Instant Flash, OC DNA, APP Charger
- Free Bundle : CyberLink MediaEspresso 6.5 Trial



Dieses Modell wird nicht in allen Regionen der Welt verkauft. Bezüglich der Verfügbarkeit in Ihrer Region kontaktieren Sie bitte Ihren Händler.

Produkt Spezifikationen

Generelles	
CPU	- Support for Socket AM3+ processors - Support for Socket AM3 processors: AMD Phenom™ II X6 / X4 / X3 / X2 (except 920 / 940) / Athlon II X4 / X3 / X2 / Sempron processors - Supports 8-Core CPU - Supports AMD OverDrive™ with ACC feature (Advanced Clock Calibration) - AMD LIVE!™ Ready - Supports AMD's Cool 'n' Quiet Technology - FSB 2600 MHz (5.2 GT/s) - Supports United Overclocking Technology - Supports Hyper-Transport 3.0 (HT 3.0) Technology
Chipsatz	- Northbridge: AMD 760G - Southbridge: AMD SB710
Arbeitsspeicher	- Dual Channel DDR3 memory technology - 2 x DDR3 DIMM slots - Supports DDR3 1800(OC)/1600(OC)/1333/1066/800 non-ECC, un-buffered memory - Max. capacity of system memory: 8GB* *Due to the operating system limitation, the actual memory size may be less than 4GB for the reservation for system usage under Windows® 32-bit OS. For Windows® 64-bit OS with 64-bit CPU, there is no such limitation.
BIOS	- 8Mb AMI Legal BIOS - Supports "Plug and Play" - ACPI 1.1 Compliance Wake Up Events - Supports jumperfree - SMBIOS 2.3.1 Support - CPU, VCCM, NB Voltage Multi-adjustment
Audio, Video und Netzwerk	
Grafik	- Integrated AMD Radeon 3000 graphics - DX10 class iGPU, Pixel Shader 4.0 - Max. shared memory 512MB - Supports D-Sub with max. resolution up to 2048x1536 @ 60Hz
Audio	- 5.1 CH HD Audio (Realtek ALC662 Audio Codec)
LAN	- PCIE x1 Gigabit LAN 10/100/1000 Mb/s - Realtek RTL8111E - Supports Wake-On-LAN - Supports PXE
Erweiterungsslots/Konnektivität	
Steckplätze	- 1 x PCI Express 2.0 x16 slot (blue @ x16 mode) - 1 x PCI Express 2.0 x1 slot - 2 x PCI slots
Anschluss	- 4 x SATA2 3.0 Gb/s connectors, support RAID (RAID 0, RAID 1, RAID 10 and JBOD), NCQ, AHCI and Hot Plug functions - 1 x ATA133 IDE connector (supports 2 x IDE devices) - 1 x Floppy connector - 1 x Print port header - CPU/Chassis/Power FAN connector - 24 pin ATX power connector - 4 pin 12V power connector - Front panel audio connector - 2 x USB 2.0 headers (support 4 USB 2.0 ports)
ATX-Blende	- I/O Panel - 1 x PS/2 Mouse Port - 1 x PS/2 Keyboard Port - 1 x Serial Port: COM1 - 1 x VGA Port - 4 x Ready-to-Use USB 2.0 Ports - 1 x RJ-45 LAN Port with LED (ACT/LINK LED and SPEED LED) - HD Audio Jack: Line in / Front Speaker / Microphone
Sonstige Features/Verschiedenes	
	- ASRock OC Tuner - ASRock Intelligent Energy Saver - ASRock Instant Boot - ASRock Instant Flash

Einzigartige Features	- ASRock Instant Flash II
	- ASRock OC DNA
	- ASRock APP Charger
	- ASRock XFast USB
	- ASRock XFast LAN
	- ASRock XFast RAM
	- Hybrid Booster:
	- CPU Frequency Stepless Control
- ASRock U-COP	
- Boot Failure Guard (B.F.G.)	
Support-CD	- Drivers, Utilities, AntiVirus Software (Trial Version), CyberLink MediaEspresso 6.5 Trial
Produktzubehör	- Quick Installation Guide, Support CD, I/O Shield
	- 2 x SATA Data Cables
Hardware überwachung	- CPU Temperature Sensing
	- Chassis Temperature Sensing
	- CPU/Chassis/Power Fan Tachometer
	- CPU Quiet Fan
	- Voltage Monitoring: +12V, +5V, +3.3V, Vcore
Formfaktor	- Micro ATX Form Factor: 9.6-in x 7.2-in, 24.4 cm x 18.3 cm
	- Solid Capacitor for CPU Power
Betriebssystem	- Microsoft® Windows® 8 / 8 64-bit / 7 / 7 64-bit / Vista™ / Vista™ 64-bit / XP / XP Media Center / XP 64-bit compliant
Zertifizierungen	- FCC, CE, WHQL
	- ErP/EuP Ready (ErP/EuP ready power supply is required)

Achtung:
Bitte beachten Sie, dass Overclocking, inklusive dem Verändern von BIOS-Einstellungen und der Nutzung von Overclockingprogrammen von Drittherstellern, immer ein gewisses Risiko birgt. Overclocking kann ihre Systemstabilität beeinflussen oder aber zu Schäden Ihrer Komponenten und Geräte führen. Die Ausführung geschieht auf eigene Gefahr und Kosten. Für Schäden die durch Overclocking verursacht werden sind wir nicht verantw örtlich.

Die Spezifikationen können ohne vorherigen Hinweis geändert werden. Die Marken und Produktnamen sind Schutzmarken der jeweiligen Firmen. Alle Konfigurationen die von den original Spezifikationen abweichen werden nicht garantiert.